## **Asphalt Plant Emission Fee Calculation Guide**

In order to calculate emission fees for an asphalt plant the following information must be known for each plant:

- 1. tons of asphalt produced in the past year.
- 2. kilowatt hours produced by the diesel generators in past year (estimate by multiplying the kW rating of the generator times the number of hours operated.)
- 3. number of gallons of diesel burned in past year.

That is all the information required to estimate the emission fees.

Provide the emission estimate to the department no later than March 31st each year.

ASPHALT PLANT EMISSION FEE CALCULATIONS	
NOx TPY (A) = tons of asphalt produced multiplied by	
0.00006 for diesel fired batch mix	0.0000125 for nat gas fired batch mix
0.0000275 for diesel fired drum mix	0.000013 for nat gas fired drum mix
CO TPY (B) = tons of asphalt produced multiplied by	
0.0002 for diesel fired batch mix	0.0002 for nat gas fired batch mix
0.000065 for diesel fired drum mix	0.000065 for nat gas fired drum mix
NOx TPY (C1) from diesel generators Multiply kW hours by 0.000020786 = C1	
CO TPY (C2) from diesel generators Multiply kW hours by 0.000004479 = C2	
$SO_2$ TPY (D) = gals of diesel burned for the year multiplied by 0.0000355	
<b>Determine Total NOx</b> $A + C1 = X$	Determine Total CO $B + C2 = Y$
If either X or Y or D is less than 10 tons do not include in calculation below.	
$NOX(X) + CO(Y) + SO_2(D) = Total emissions in tons per year (TPY)$	
Total emissions (TPY) x \$12.52 = Emission Fee in \$	

Send Emission Estimate to: ADEC Air Permits Assessable Emission Estimate 410 Willoughby Avenue, Suite 303 Juneau, Alaska 99801

Or FAX to (907) 465 5129 PLEASE MARK FAX "EMISSION FEE ESTIMATE"